

## Mini DisplayPort® to HDMI® Video Adapter Converter - White

StarTech ID: MDP2HDW



The MDP2HDW passive Mini DisplayPort® to HDMI® Video Adapter/Converter (White) offers a convenient HDMI/Mini-DisplayPort link, which enables you to connect an HDMI computer monitor or television to a device with a Mini-DisplayPort output, while saving the expense of upgrading the monitor for compatibility.

The adapter supports high resolution output up to 1920x1200, offering a high quality solution for mirroring or extending a computer desktop onto a second display.

This versatile Mini DisplayPort to HDMI adapter requires a multimode DisplayPort port (DisplayPort ++)  
connection to function, and is compatible with Intel® Thunderbolt™; output when connected directly to a supporting DisplayPort over Thunderbolt™; I/O port.

This adapter allows for audio pass-through if supported by the video source. Please review the video source manual to confirm support.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays
- Keep your existing HDMI® monitor to be used with your new Mini-DisplayPort® device
- Ideal for using your HDMI monitor as a secondary display

## Features

- Supports PC resolutions up to 1920x1200 and HDTV resolutions up to 1080p
- Easy to use passive cable, no software required
- Compatible with Intel® Thunderbolt™

## Technical Specifications

Warranty	2 Years
Converter Type	Passive
Adapter Style	Adapter
Audio	Yes
Industry Standards	DisplayPort 1.1a HDMI 1.3a
Connector A	1 - Mini-DisplayPort (20 pin) Male
Connector B	1 - HDMI (19 pin) Female
Maximum Digital Resolutions	1920x1200 / 1080p
Audio Specifications	5.1 Surround Sound
System and Cable Requirements	DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported)
Color	White
Cable Length	4.7 in [120 mm]
Product Length	6.7 in [170 mm]
Product Width	1.6 in [40 mm]
Product Height	0.6 in [15 mm]
Product Weight	10.5 oz [298 g]
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Humidity	40~85% RH
Shipping (Package) Weight	0.1 lb [0.1 kg]
Included in Package	1 - Mini-DisplayPort® to HDMI® converter

Certifications, Reports and Compatibility

