



Tripp Lite
1111 W. 35th Street

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

QSFP+ to QSFP+ 40Gb Passive DAC Copper Infiniband Cable, 2M (6-ft.)

MODEL NUMBER: N282-02M-BK



Description

Tripp Lite's 2m QSFP+ (QSFP Plus) 40GBASE-CR4 / 802.3ba qualified passive copper cable provides next generation performance by combining four 10 Gb/s SFP+ channels into one affordable high-density package. Our QSFP+ cables integrate a new 40G Ethernet-optimized (40GbE) 38-position "board-as-connector" design, with zinc die-cast backshells for superior EMI resistance, minimal insertion loss, and improved cross-talk performance. Cable featuress 8-pair wire technology optimized for bandwidth-intense applications including 40-Gigabit Ethernet (40GBASE-CR4), 6G SAS, Fibre Channel and SONET. Flexible 24 AWG conductors maintain a smooth, high-frequency response (20 GHz). Each 2m (6.56-ft) length QSFP+ cable goes through a rigorous assembly and test procedure aimed at eliminating unnecessary signal loss. Our cables are fully compliant to the QSFP+ MSA and SFF-8436 architecture for guaranteed compatibility with all QSFP and QSFP+ ports.

Features

- 2 Meter QSFP+ tp QSFP+ 40Gb Passive DAC Copper Infiniband cable
- Meets or Exceeds strict 40-Gigabit Ethernet 40GBase-CR4 standards
- SDR, DDR, and QDR Compatible
- QSFP+ to QSFP+ 30AWG SFF-8436 compliant cable and connector
- Up to 10.3125 Gbps transfer rate per channel (40Gb aggregate)
- . Multi-platform support for 40Gb, SAS, Fibre Channel, and SONET
- Zinc die-cast QSFP+ connectors with "Pull-to-Release" latching
- Fully compliant to latest QSFP+ MSA (Multi Source Agreement)
- Lower port cost and reduced power budget vs Fiber Optics
- RoHS, SFF-8436, and IEEE 802.3ba Compliant
- BER better than 10¹²

Highlights

- 40Gbps QSFP+ to QSFP+ 2
 Meter patch cable
- Meets or Exceeds 40-Gigabit Ethernet 4oGBASE-CR4 standards
- Fully compliant to the latest QSFP+ MSA (Multi Source Agreement)
- . SDR, DDR, and QDR Compatible

Applications

- Storage Area Networks (SAN)
- Data Center Cabling
 Infrastructure
- High Density Connections
- Switched fabric I/O (Ultra High Bandwidth Switches & Routers)

System Requirements

 Networking Switch or other hardware with open QSFP+ Port(s)

Package Includes

 2 Meter, QSFP+ to QSFP+ High Speed Passive Copper 40GB Cable

Specifications





| OVERVIEW | |
|-------------------------------------|---------------------------------|
| Model Type | QSFP+ |
| INPUT | |
| Cable Length (ft.) | 7 |
| Cable Length (m) | 2 |
| PHYSICAL | |
| Color | Black |
| CONNECTIONS | |
| Connector A | QSFP+ (MALE) |
| Connector B | QSFP+ (MALE) |
| CERTIFICATIONS | |
| Certifications | MSA SFF-8436 and RoHS compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.