

Cisco 110 Series Unmanaged Switches

Affordable, Easy-to-Use Switches for Small Business Networks, with Zero Configuration Required

Highlights

- Affordable 10/100/1000-Mbps speeds for even the most bandwidth-hungry applications
- 5 to 24-port models that are desktop or rack mountable
- Power over Ethernet models to provide power to IP phones, Access points, and other devices
- Works right out of the box—plug-and-play and no set up

Product Overview

Give your office network a boost of speed and performance at a low price that takes almost no time to set up. Easily build a highly reliable network to connect your computers, printers, copiers, and other office equipment. If your business is like most small companies, you don't have an IT staff to set up your network for you. Now you can have a high-performance, business-class office network that just works, right out of the box, with the Cisco 110 Series Unmanaged Switches. Users, workgroups, labs, departments, or growing offices can now deliver large amounts of multimedia, image, and video information across the network in no time at all.

Cisco 110 Series Unmanaged switches deliver basic network connectivity and reliability for small businesses that's easy on the budget and without all the complexity. These switches provide all of the features, expandability, and investment protection you expect from Cisco, with no installation software and nothing to configure. Just plug it in, connect your computers and other business equipment, and get to work.

Cisco 110 Series Unmanaged switches (Figure 1), part of the Cisco Small Business networking solutions, are a line of unmanaged switches that provide wire-speed Fast Ethernet and Gigabit Ethernet connectivity to connect your small business office. Available in desktop and rack-mount models, these switches are designed to suit any office space with basic network needs and to optimize power efficiency. They use less power and provide the robust, reliable connectivity your business demands, as well as support for advanced features such as quality of service (QoS), Loop Detection, and Cable Diagnostics—all in a switch that you can set up yourself, in minutes. A business-class, affordable network solution, Cisco 110 Series switches bring the proven reliability and investment protection of Cisco networking solutions to your small business.

Figure 1. Cisco 110 Series Unmanaged Switches



Features

Cisco 110 Series switches provide an easy-to-use solution for your small business network. They offer:

- **Ease of use:** Cisco 110 Series switches work right out of the box, with no software to install and nothing to configure. Each switch port independently sets itself for the optimal speed and determines whether to run in half- or full-duplex mode automatically. As a standards-based Cisco solution, Cisco 110 Series switches are also designed to immediately accommodate all of the devices in your network, including:
 - Support for 10 megabits per second (Mbps), 100 Mbps, and up to 1 gigabit per second (1000 Mbps) devices in the same network
 - Automatic cable detection, so you don't have to worry about using the wrong cable type
 - Compatibility with network devices from other vendors
- **Simple setup:** Designed for small office spaces, Cisco 110 Series switches are available in both compact desktop and rack-mount models. The desktop models offer a wall-mount option for discreet mounting under a desk or on the wall of an office or conference room.
- **High performance:** Cisco 110 Series switches deliver the performance you need to run your business applications - including bandwidth-intensive video services - and avoid slow and sluggish networks. It supports up Gigabit Ethernet speeds, unlocking a new level of capacity and performance in your business network and letting you transfer large files in seconds.
- **Reduced energy costs:** Cisco 110 Series switches are designed to help conserve energy by optimizing power use without compromising performance, which protects our environment and reduces your energy costs. In addition, they support the Energy Efficient Ethernet (IEEE 802.3az) standard, which reduces energy consumption by monitoring the amount of traffic on an active link and putting the link into a sleep state during quiet periods. Most of the switches have no fans, so they run silently and unobtrusively while lowering energy costs.
- **Power-over-Ethernet:** Cisco 110 Series switches are available with PoE ports on both Fast Ethernet and Gigabit Ethernet models. This capability simplifies the deployment of IP telephony, wireless, video surveillance, and other solutions by allowing you to connect and power network endpoints over a single

Ethernet cable. With no need to install separate power supplies for IP phones or wireless access points, you can take advantage of advanced communications technologies more quickly, and at a lower cost.

- **Support for advanced technologies:** All switches include advanced Cisco traffic-handling features to keep your applications running at peak performance. Integrated QoS intelligence on all models automatically prioritizes delay-sensitive services such as voice or video to improve your network's performance. Loop Detection helps discover loops in the network that you may have accidentally created, thus avoiding broadcast storms that will bring your network to a stall. Cable Diagnostics help to quickly identify and troubleshoot network cabling faults and issues. Fast store-and-forward switching identifies damaged packets and prevents them from being passed on through the network. All of these features run automatically, with no management or configuration required.
- **Peace of mind:** Cisco 110 Series switches deliver the rock-solid reliability you expect from a Cisco switch. The solution has been rigorously tested to ensure optimal uptime and performance. In addition, Limited Lifetime hardware warranty provides peace of mind.

Specifications

Table 1 lists the specifications, package contents, and minimum requirements for the Cisco 110 Series

Table 1. Specifications for the Cisco 110 Series Switches.

Specifications	Description
Standards	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, IEEE 802.3z Gigabit Ethernet, IEEE 802.3x Flow Control, 802.1p priority, Energy Efficient Ethernet, 802.3af, Power Over Ethernet
Cabling type	Category 5e or better
LED indicators	System/PWR, Link/Activity, 100M,* PoE, *Max PoE, Cable Diagnostics, Loop Detection, Gigabit,* mini-GBIC* *if present
Physical Interfaces	
Ports	10/100/1000 Ethernet, with support for 802.3af PoE, Power Port for AC adapter or Power cord
Power Supply	SF110D-05, SF110D-08: DC 12V, 500mA SF110D-16, SG110D-08, SG110D-05: DC 12V, 1.0A SF110D-08HP, SG110D-8HP: DC 48V. 1.25A SF110-16, SF110D-16HP, SF110-24, SF112-24, SG110-16, SG110-16HP, SG110-24, SG110-24HP, SG112-24: 110-240VAC, 50-60 Hz, internal, universal
Lock slot	Slot for Kensington lock
Physical Specifications	
Physical dimensions (W x D x H)	SF110D-05: 3.65 x 1.06 x 3.57 inches (92.6 x 27 x 90.6 mm) SF110D-08: 5.12 x 1.06 x 5.12 inches (130 x 27 x 130 mm) SF110D-08HP: 6.29 x 1.18 x 5.05 inches (160 x 30 x 128.5 mm) SF110D-16: 5.12 x 1.52 x 5.12 inches (130 x 38.5 x 130 mm) SF110-16: 11 x 1.75 x 6.7 inches (279.4 x 44.5 x 170 mm) SF110D-16HP: 6.29 x 3.54 x 1.69 inches (160 x 90 x 43 mm) SF110-24: 11 x 1.75 x 6.7 inches (279.4 x 44.5 x 170 mm) SF112-24: 17.35 x 1.74 x 7.99 inches (440.6 x 202.82 x 44.32 mm) SG110D-05: 4.33 x 1.18 x 3.93 inches (110 x 30 x 110 mm) SG110D-08: 5.51 x 1.31 x 5.51 inches (140 x 33.35 x 140 mm) SG110D-08HP: 6.29 x 1.18 x 5.05 inches (160 x 30 x 128.5 mm) SG110-16: 11 x 1.75 x 6.7 inches (279.4 x 44.5 x 170 mm) SG110-16HP: 11 x 1.75 x 6.7 inches (279.4 x 44.5 x 170 mm)

Specifications	Description		
	SG110-24: 17.35 x 1.74 x 7.99 inches (440.6 x 202.82 x 44.32 mm) SG110-24HP: 17.35 x 1.74 x 7.99 inches (440.6 x 202.82 x 44.32 mm) SG112-24: 11 x 1.75 x 6.7 inches (279.4 x 44.5 x 170 mm)		
Weight	SF110D-05: 0.47 lb. (0.22 kg) SF110D-08: 0.83 lb. (0.38 kg) SF110D-08HP: 1.2 lb. (0.545 kg) SF110D-16: 1.03 lb. (0.46 kg) SF110-16: 2.79 lb. (1.25 kg) SF110D-16HP: 0.99 lb. (0.45 kg) SF110-24: 2.91 lb. (1.32 kg) SF112-24: 4.93 lb. (2.00 kg) SG110D-05: 0.70 lb. (0.32 kg) SG110D-08: 0.94 lb. (0.43 kg) SG110D-08HP: 1.2 lb. (0.55 kg) SG110-16: 3.15 lb. (2.13 kg) SG110-16HP: 4.15 lb. (1.43 kg) SG110-24: 3.59 lb. (1.63 kg) SG110-24HP: 4.59 lb. (2.43 kg) SG112-24: 5.05 lb. (2.3 kg)		
Ports	SF110D-05: 5 RJ-45 connectors for 10BASE-T/100BASE-TX SF110D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX SF110D-08HP: 8 RJ-45 connectors for 10BASE-T/100BASE-TX; SF110D-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX SF110D-16HP: 16 RJ-45 connectors for 10BASE-T/100BASE-TX SF110-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX SF110-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX SF112-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX; with 2 combo mini-GBIC slots SG110D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG110D-08HP: 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG110-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG110-16HP: 16 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports SG110-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots SG110-24HP: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots SG112-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots All units: Automatic medium dependent interface (MDI) and MDI crossover (MDI-X); auto negotiated port for connecting 10-, 100-, 1000- Mbps devices		
Power over Ethernet (PoE)	Model Name	Power Dedicated to PoE	Number of PoE Ports
	SF110D-08HP	32 Watts	4
	SF110D-16HP	64 Watts	8
	SG110D-08HP	32 Watts	4
	SG110-16HP	64 Watts	8
	SG110-24HP	100 Watts	12
Fan/Fan-less Models	All models have no fans and are fan-less, except for SG100-24HP		
Performance			
Switching capacity	SF110D-05: 1 Gbps SF110D-08: 1.6 Gbps SF110D-08HP: 1.6 Gbps SF110D-16: 3.2 Gbps SF110-16: 3.2 Gbps SF110D-16HP: 3.2 Gbps		

Specifications	Description
	SF110-24: 4.8 Gbps SF112-24: 8.8 Gbps SG110D-05: 10 Gbps SG110D-08: 16 Gbps SG110D-08HP: 16 Gbps SG110-16: 32 Gbps SG110-16HP: 32 Gbps SG110-24: 48 Gbps SG110-24HP: 48 Gbps SG112-24: 48 Gbps
Forwarding capacity	Forwarding rate in million packets per second (mpps) (based on 64-byte packets): SF110D-05: 0.74 mpps SF110D-08: 1.4 mpps S110D-08HP: 1.2 mpps SF110D-16: 1.4 mpps SF110-16: 1.4 mpps SF110D-16HP: 1.4 mpps SF110-24: 3.6 mpps SF112-24: 6.5 mpps SG110D-05: 7.4 mpps SG110D-08: 11.9 mpps SG110D-08HP: 11.9 mpps SG110-16: 23.8 mpps SG110-16HP: 23.8 mpps SG110-24: 35.7 mpps SG110-24HP: 35.7 mpps SG112-24: 35.7 mpps
Capabilities	
Head-of-line (HOL) blocking	HOL blocking prevention
Jumbo Frame	9216 bytes
Quality of Service (QoS)	802.1p priority based, 4 hardware queues, priority queuing and weighted round-robin (WRR)
Loop Detection	Helps discover loops in the network to avoid broadcast storms
Cable Diagnostics	Quickly identify and troubleshoot network cable faults and/or shorts
Mounting and Physical Security	
Mounting options	Desktop or rack mount
Physical security lock	Kensington lock slot
Environmental	
Compliance/Certifications	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A, FCC Class B* *select models
Operating temperature	32° to 104°F (0° to 40°C)
Storage temperature	-4° to 158°F (-20° to 70°C)
Operating humidity	10% to 90%, relative, non-condensing
Storage humidity	5% to 90%, relative, non-condensing
System memory	128-MB RAM 128-MB Flash
Package Contents	
<ul style="list-style-type: none"> • Cisco 110 Series Switch • Power cord/power adapter 	

Specifications	Description
<ul style="list-style-type: none"> Quick-start guide Mounting hardware 	
Minimum Requirements	
<ul style="list-style-type: none"> Devices Supporting 802.3 Ethernet, 802.u Faster Ethernet, or 802.3ab Gigabit Ethernet Cat5 or better Ethernet Cable Network Interface Card for each computer 	
Warranty	
Cisco 110 Series Switch	Limited lifetime

Ordering Information

Table 2 gives ordering information for the Cisco 110 Series Unmanaged Switches

Table 2. Ordering Information for Cisco 110 Series Unmanaged Switches

Part Number	Description
SF110D-05	Cisco SF110D-05 - 5-Port 10/100 Desktop Switch
SF110D-08	Cisco SF110D-08 8-port 10/100 Desktop Switch
SF110D-08HP	Cisco SF110D-08P 8-port 10/100 PoE Desktop Switch
SF110D-16	Cisco SF110D-16 16-port 10/100 Desktop Switch
SF110D-16HP	Cisco SF110D-16P 16-port 10/100 PoE Desktop Switch
SF110-16	Cisco SF110-16 16-Port 10/100 Switch
SF110-24	Cisco SF110-24 24-Port 10/100 Switch
SF112-24	Cisco SF112-24 24-port 10/100 + 2 Mini-GBIC & 2 GE Uplink
SG110D-05	Cisco SG110D-05 5-port Gigabit Desktop Switch
SG110D-08	Cisco SG110D-08 8-Port Gigabit Switch
SG110D-08HP	Cisco SG110D-08P 8-Port Gigabit PoE Switch
SG110-16	Cisco SG110-16 16-Port Gigabit Switch
SG110-16HP	Cisco SG110-16HP 16-Port PoE Gigabit Switch
SG112-24	Cisco SG112-24 COMPACT 24-port Gig Switch-2 Mini-GBIC Ports
SG110-24	Cisco SG110-24 24-port Gigabit Switch + 2 Mini GBIC Ports 1U
SG110-24HP	Cisco SG110-24HP 24-Port PoE Gigabit Switch

Cisco Limited Lifetime Warranty for Cisco Small Business Products

This Cisco Small Business product comes with a limited lifetime hardware warranty. Product warranty terms and other information applicable to Cisco products are available at <http://www.cisco.com/go/warranty>.

Services for Small Business

Reduce downtime with fast, expert technical support and flexible hardware coverage. Cisco Services improve network availability and help you get the most value from your Cisco products. Service plans for your Cisco Small Business products provide more support than a product warranty. A warranty protects you against product defects,

and a majority of support calls are unrelated to faulty materials or manufacturing. Most callers ask about product features, technical problems, or how to expand their network.

Cisco offers an unlimited number of calls and no restrictions on call duration, so you can get the help you need, and the most from your Cisco product.

For more information on Cisco Services, see <http://www.cisco.com/go/sbs>.

For More Information

For more information on Cisco Small Business products and solutions, visit <http://www.cisco.com/smallbusiness> or <http://www.cisco.com/go/110Switches>




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)