# 4 Port Black SuperSpeed USB 3.0 Hub

*StarTech ID: ST4300USB3EU*



The ST4300USB3EU 4-Port SuperSpeed USB 3.0 Hub allows you to add 4 additional USB 3.0 ports from a single USB 3.0 connection to the host computer system.

Backward compatible with USB 2.0 and USB 1.x standards, this USB 3.0 hub still supports older USB devices and can also be used as a hub on older systems that do not have USB 3.0 ports.

With the capability to mix and match USB 3.0/2.0/1.x devices and be used with or without the included external power adapter, this hub offers the best of versatility and portability.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

**Användning**

- Expand your USB 3.0 capabilities with additional ports
- Make hard to access USB ports more accessible by being able to position the hub anywhere the cable will reach
- Extend the range of a USB device by having the hub act as a mid-point repeater

**Funktioner**

- Four USB type 'A' ports that can each be accessed simultaneously
- SuperSpeed USB 3.0 compliant, with data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- Supports USB 3.0/2.0/1.x devices simultaneously at full bandwidth
- Provides up to 900mA of power per port
- Compact, desktop-style form factor
- Plug-and-Play and hot-swap compatible

**Tekniska specifikationer**

| | |
|---|---|
| Warranty | 2 Years |
| Ports | 4 |
| Interface | USB 3.0 |
| Chipset ID | VLI - VL810 |
| External Ports | 1 - USB 3.0 B (9 pin; SuperSpeed) Female |
| External Ports | 4 - USB 3.0 A (9 pin; SuperSpeed) Female |
| Maximum Data Transfer Rate | 5 Gbps |
| OS Compatibility | OS Independent; No additional drivers or software required |
| System and Cable Requirements | USB 3.0 or 2.0 or 1.x compliant host controller with available port. |
| **Note** | If used with the Apple Mac OS operating system, this device will function in USB 2.0 mode only |
| Color | Black |
| Enclosure Type | Plastic |
| Product Length | 95 mm [3.7 in] |
| Product Width | 68 mm [2.7 in] |
| Product Height | 23 mm [0.9 in] |
| Product Weight | 55 g [1.9 oz] |
| LED Indicators | 1 - Power (Blue) |
| Power Source | AC Adapter Included |
| Input Voltage | 110 ~ 240 AC |
| Output Voltage | 5 DC |
| Output Current | 2A |
| Center Tip Polarity | Positive |
| Plug Type | M |
| Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Humidity | 5~85% RH |
| Shipping (Package) Weight | 0.4 kg [1 lb] |
| Included in Package | 1 - USB 3.0 Hub |
| Included in Package | 1 - USB 3.0 cable |
| Included in Package | 1 - Power Adapter |
| Included in Package | 1 - Instruction Manual |

**Certifikat, rapporter och kompatibilitet**

CE

FC

OperatingSystem
Independent

RoHS Compliant
Available