

AXIS F1004 Bullet Sensor Unit

Small bullet-style design for easy installation

AXIS F1004 Bullet Sensor Unit has a highly compact bullet-style design for easy and discreet installation on indoor ceilings and walls. It can rotate and tilt to the desired viewing direction. AXIS F1004 Bullet comprises a fixed lens and an image sensor. It offers a 102° horizontal field of view, a 720p video resolution, and good low-light performance. It has a detachable 8-m (26 ft) cable for connection to an AXIS F Main Unit.

- > **Easy and discreet installation**
- > **Rotates and tilts to the desired viewing direction**
- > **102° horizontal field of view**
- > **HDTV 720p resolution**



AXIS F1004 Bullet Sensor Unit

Camera		General	
Image sensor	1/4" (effective) progressive scan RGB CMOS	Casing	Plastic
Lens	Fixed iris 2.1 mm, F2.2 Horizontal angle of view: 102° Vertical angle of view: 56°	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Resolutions	Max 1280x720	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Wide dynamic range	WDR	Approvals	IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 50581, IEC 60529 IP3x, EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24
Minimum illumination	Color 0.4 lux	Dimensions	60 x 60 x 89 mm (2 3/8 x 2 3/8 x 3 1/2 in)
Shutter time	1/24500 s to 1/6 s	Weight	55 g (0.12 lb)
Camera angle adjustment	Pan: ±180° Tilt: 0 to 90° Rotation ±90°	Required hardware	AXIS F Main Unit
Frame rate	Max 25/30 fps (50/60 Hz)	Included accessories	Installation Guide
		Optional accessories	AXIS F7315 Cable White 15 m
		Warranty	Axis 3-year warranty, see www.axis.com/warranty

Environmental responsibility:

www.axis.com/environmental-responsibility