

4 Port USB to RS232 Serial DB9 Adapter Hub

StarTech ID: ICUSB2324



This 4 Port USB to RS232 Serial Hub lets you connect up to four RS232 serial devices to your Mac or PC laptop or desktop computer through a single USB port, as though the computer offered built-on DB9M serial connectors.

The RS232 Serial Hub is compactly designed to preserve valuable workspace, and is bus-powered to eliminate the need for an external power adapter.

A cost-effective solution that bridges the compatibility gap between modern USB-capable computers and legacy RS232 serial peripherals, this dependable USB/RS232 Serial Adapter hub is backed by StarTech.com's Lifetime Warranty.

Applications

- Connect modems, digitizer tablets, mice, bar code scanners, GPS receivers, ISDN terminal adapters, mobile phones, scanners, UPSes and POS equipment to your system
- Connect and program LED and Digital signage boards with serial communication ports

Features

- Bus powered, no external power adapter required
- Easy Plug-and-Play installation
- Fully compliant with USB 1.1 specifications and compatible with USB 2.0
- Provides you with four additional Straight-Through RS232 serial ports

Technical Specifications

Warranty	Lifetime
Ports	4
Interface	Serial
Bus Type	USB 2.0
Port Style	External Hub
Industry Standards	RS232
Industry Standards	USB 1.1
Chipset ID	FTDI - FT232RL
Connector Type(s)	1 - USB A (4 pin) Male
External Ports	4 - DB-9 (9 pin; D-Sub) Male
Serial Protocol	RS-232
Max Baud Rate	921.6 Kbps
FIFO	256 Bytes
OS Compatibility	Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), 2000, 98SE, XP Embedded, CE (4.2+) Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.x (Tested up to 10.10) Linux 2.4.x / 2.6.x
System and Cable Requirements	One free USB port
Enclosure Type	Plastic
Cable Length	6 ft [1.8 m]
Product Length	5.9 in [150 mm]
Product Width	2.6 in [66.5 mm]
Product Height	1 in [26 mm]
Product Weight	3.9 oz [110 g]
Power Consumption	1 ~ 1.5W
Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20 to 85°C (-4 to 185°F)
Humidity	5~95% RH
Shipping (Package) Weight	0.8 lb [0.4 kg]
Included in Package	1 - 4 Port Serial Hub
Included in Package	1 - USB Cable

Included in Package	1 - Driver CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

