

10GbE Pass-Through Cassette - (x12) LC Duplex

MODEL NUMBER: **N484-12LC**



Highlights

- High Density Fiber Cassette for use with the [N484-00U](#) and [N484-01U](#) chassis'
- 10GbE Pass-Through Cassette, with(x12) LC Duplex connections
- Complies with IEEE 802.3ae(10GbE) and ANSI T11.2(Fibre Channel) requirements

Package Includes

- N484-12LC 10Gb Pass-Through Cassette - (x12) LC Duplex
- Quick Start Guide

Description

Tripp Lite's N484-12LC is a High Density 10Gb Pass-through Cassette with(x12) LC Duplex connections. Designed specifically for use with Tripp Lite's [N484-00U](#) and [N484-01U](#) chassis'; up to 4 cassettes per [N484-01U](#), or 1 per [N484-00U](#). Each duplex LC connection is rated for 10GbE, with an extremely low max insertion loss of 0.35db, well under the IEEE 802.3ae maximum channel loss spec of <25db. Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required. Furthermore, each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations. Cassette housing is manufactured with heavy duty, 1.0mm Cold Rolled Steel.

Features

- High Density Fiber Cassette for use with the [N484-00U](#) and [N484-01U](#) chassis'
- 10GbE Pass-Through Cassette, with(x12) LC Duplex connections
- Complies with IEEE 802.3ae(10GbE) and ANSI T11.2(Fibre Channel) requirements
- Max insertion loss of 0.35dB falls well under the IEEE 802.3ae maximum channel loss spec of <25dB
- Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required
- Each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations.
- Housing made of heavy duty, 1.0mm Cold Rolled Steel
- Includes dust caps for unused ports

Specifications

PHYSICAL	
Unit Dimensions (hwd / in.)	1.4 x 4.4 x 0.9
Unit Weight (lbs.)	0.3
Color	Black
ENVIRONMENTAL	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Operating Temperature Range	-4 to 122 F (-20 to 50 C)
CONNECTIONS	
Ports	12
Side A - Connector 1	(12) LC DUPLEX (FEMALE)
Side B - Connector 1	(12) LC DUPLEX (FEMALE)
CERTIFICATIONS	
Approvals	RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>