

SmartRack 12U Slim Wall-Mount Shallow-Depth Rack Enclosure Cabinet

MODEL NUMBER: SRW12U13



Highlights

- Slim design for shallow network switches and patch panels
- 12U with dual threaded front rails
- Locking, reversible front door
- Locking, removable side panels
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements
- Interior vertical posts have square holes for cage nuts plus 12-24 threaded mounting holes

Package Includes

- SRW12U13 Wallmount Rack Enclosure
- Mounting Hardware
- Keys
- Owner's Manual

Description

The SRW12U13 slim 12U Wall-Mount Rack Enclosure is designed to safely store shallow network switches and patch panels. It integrates wall-mounting, easy equipment access and cable management in Telco environments with limited floor space. Ventilated top and bottom panels allows generous airflow to keep equipment operating safely. Top panel offers a convenient cable access cutout with cover. Adjustable front mounting rails have square holes (default position) and tapped holes to accommodate 12U of equipment. A sturdy wall-mount bracket allows the cabinet to quickly be hung on the wall and supports up to 200lbs of equipment. The SRW12U13 comes with a 5-year product warranty.

Features

- 12U slim wall-mounted enclosure
- Dual threaded rail option
- Ventilated top and bottom panels for increased airflow
- Locking, reversible front door
- Locking, removable side panels
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements

Specifications

General Info	
RoHS	Y
OVERVIEW	
Style	Wall Mounted



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL	
Installed Whole System Maximum Rack Depth (in.)	13
Rack Height (U Spaces)	12
Shipping Dimensions (hwd / in.)	27.56 x 25.6 x 15.75
Shipping Weight (lbs.)	40
Unit Dimensions (hwd / in.)	25.08 x 23.62 x 13
Unit Weight (lbs.)	38
Color	Black
Weight Capacity - Stationary (lbs.)	200
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
Hinged (Swings Away from Wall Bracket)	No
SPECIAL FEATURES	
Grounding Lug	Front door frame
CERTIFICATIONS	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.