

## SmartRack 12U Wall-Mount Open Frame Rack

MODEL NUMBER: SRWO12UHD



### Highlights

- Open frame with 2 post mounting, 19" Width, 18" Depth
- Threaded (12-24) mounting holes
- Heavy duty steel frame
- Easy assembly

### Package Includes

- (1) 3mm L-Shaped Hex Key
- (2) Top/Bottom Panel Frames
- (2) Vertical Mounting Rails
- (8) M5 Button Head Cap Screws
- (24) #12-24 Equipment Mounting Screws

### Description

Designed with provisions to integrate wall mounting, easy equipment access and cable management, SmartRack wall-mounted open frame cabinets are perfect for network equipment in IT environments with limited floor space. The 19" wide open frame rack is a heavy-duty, open frame rack designed for secure, high density servers and networking applications in IT environments.

### Features

- 2-post wall mounting...EIA 19" width
- Threaded (12-24) mounting holes
- Heavy duty steel construction with diagonal support straps
- Durable black textured powder coat finish
- Easy Assembly

## Specifications

OVERVIEW	
Style	Wall Mounted
PHYSICAL	
Installed Whole System Maximum Rack Depth (in.)	18
Installed Whole System Maximum Rack Depth (cm)	45.72
Rack Height (U Spaces)	12
Shipping Dimensions (hwd / in.)	4 x 22 x 23.8
Shipping Dimensions (hwd / cm)	10.16 x 55.88 x 60.45



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Shipping Weight (lbs.)	15.4
Shipping Weight (kg)	6.98
Unit Dimensions (hwd / in.)	24.8 x 20.1 x 18.24
Unit Weight (lbs.)	14.3
Unit Weight (kg)	6.48
Unit Dimensions (cm)	EXTERNAL DIMENSIONS: 63 x 51 x 46.3(HWD)
Color	Black
Weight Capacity - Stationary (lbs.)	200
Weight Capacity - Stationary (kg)	90.718
Hinged (Swings Away from Wall Bracket)	No
<b>CERTIFICATIONS</b>	
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.