

## 48U Heavy-Duty 4-Post SmartRack Open Frame Rack - Organize and Secure Network Rack Equipment

MODEL NUMBER: **SR4POST48HD**



### Highlights

- 48U Heavy-Duty 4-post open frame rack
- Black steel with square, numbered mounting holes
- Toolless button holes to accept PDUs or cable managers

### Package Includes

- SR4POST48HD Heavy-Duty 4-Post Open Frame Rack
- Installation hardware
- (2x) PDU/Cable management brackets
- Owner's manual with warranty information

### Description

Tripp Lite's 48U Heavy-Duty 4-Post Open Frame Rack helps IT managers organize their equipment array and provides fast, easy access to installed IT equipment. The SR4POST48HD is a simple solution for housing IT equipment in secure environments and other areas that don't require a lockable rack solution. This 48U rack features heavy-duty cold-rolled steel construction with a black powder-coated finish for durability. It supports stationary loads up to 3000 lb. The SR4POST48HD comes with all the hardware required for assembly and has a self-squaring design with bolt-down provisions. For high-density applications, multiple units can be bolted together side by side.

The open design of the SR4POST48HD provides unobstructed airflow and easy access to equipment and cabling. It has numbered, square-hole mounting positions for easy installation of standard 19-inch rack equipment. The SR4POST48HD supports equipment depths up to 35 inches. This rack also accommodates toolless button-hole mounting for vertical PDUs and cable managers.

The optional [SRCASTERHDKIT](#) Heavy-Duty Rolling Caster Kit adds mobility to the SR4POST48HD. The rack supports rolling loads of 3000 lb. The SR4POST48HD also supports optional side panels with the [SR48SIDE4PHD](#), a set of two half-size side panels that add a finished look to end-of-row racks in your data center.

### Features

- Weight capacity of 3000 lbs. stationary
- Supports equipment depths up to 35 inches
- Textured, black powder coat finish
- Heavy-duty cold-rolled steel construction
- Numbered mounting positions
- Bolt down provisions
- Self-squaring design
- Easy assembly
- Optional [SRCASTERHDKIT](#) heavy-duty caster kit permits mobile use of 3,000 lb rolling loads



- Optional [SR48SIDE4PHD](#) side panels for end-of-the-row aesthetics

## Specifications

PHYSICAL	
Rack Height (U Spaces)	48
Maximum Device Depth (in.)	35.25
Maximum Device Depth (cm)	89.54
Shipping Dimensions (hwd / in.)	6.75 x 9.5 x 93.75
Shipping Dimensions (hwd / cm)	17.15 x 24.13 x 238.13
Shipping Weight (lbs.)	117
Shipping Weight (kg)	52.65
Unit Dimensions (hwd / in.)	90 x 24 x 35.25
Unit Dimensions (hwd / cm)	228.6 x 60.96 x 89.54
Unit Weight (lbs.)	110
Unit Weight (kg)	49.5
Color	Black
Weight Capacity - Stationary (lbs.)	3000
Weight Capacity - Stationary (kg)	1350
CERTIFICATIONS	
Approvals	EIA-310-D, IEC 60297-3-100, RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>