

## Cisco SFP-10G-LR Compatible 10GBase-LR LC SFP Transceiver, DDM, Singlemode, 1310 nm, 10 km

MODEL NUMBER: N286-10GLR-SLC



### Description

The N286-10GLR-SLC Cisco SFP-10G-LR Compatible 10GBase-LR LC SFP Transceiver with a duplex LC female connector functions just like the Cisco® SFP-10G-LR transceiver module and is designed to operate with Cisco networking equipment. It also meets or exceeds the SFP-10G-LR's original specifications and complies with MSA standards.

This 10GBase-LR transceiver is fully hot-pluggable, so you can install it without shutting down the network or rebooting your device. It supports data transfer rates up to 10 Gbps with 1310 nm wavelength signaling. It transmits across six miles (10 kilometers) of 9/125 SMF cabling. Its metallic housing allows low EMI.

The N286-10GLR-SLC also supports DDM (Digital Diagnostic Monitoring) and is electrical interface-compliant with SFF-8431 specification. It supports up to 11.1 Gbps bi-directional communication.

### Features

#### 10GBase-LR Transceiver with Duplex LC Connector

- Hot-pluggable for installation without rebooting or shutting down
- Supports data transfer rates up to 10 Gbps
- Transmits up to 6 mi. (10 km) with 9/125 SMF cabling
- Metallic housing for low EMI
- Supports up to 11.1 Gbps bi-directional communication
- Supports Digital Diagnostic Monitoring
- Electrical interface-compliant with SFF-8431 specification
- 1310 nm wavelength signaling

#### Designed for Use with Cisco Networking Equipment

- Functionally equivalent to Cisco SFP-10G-LR

### Highlights

- Supports data transfer rates up to 10 Gbps
- Transmits up to 6 mi. (10 km) with 9/125 SMF cabling
- Supports Digital Diagnostic Monitoring
- Complies with MSA standards
- 100% compatible with Cisco networking hardware

### System Requirements

For a list of compatible switches, see the Switch Compatibility document in the Resources tab or the Technical Support page.

### Package Includes

- N286-10GLR-SLC Cisco SFP-10G-LR Compatible 10GBase-LR LC SFP Transceiver
- Owner's manual



- Meets or exceeds SFP-10G-LR specs
- Complies with MSA standards

## Specifications

OVERVIEW	
Accessories Type	Transceiver
PHYSICAL	
Unit Dimensions (hwd / in.)	0.33 x 0.52 x 2.24
Unit Dimensions (hwd / cm)	0.84 x 1.32 x 5.69
Unit Weight (lbs.)	0.05
Unit Weight (kg)	0.02
ENVIRONMENTAL	
Storage Temperature Range	-40 to 185 F (-40 to 85 C)
Relative Humidity	10 to 85% RH, Non-Condensing
Operating Temperature	32 to 158 F (0 to 70 C)
COMMUNICATIONS	
Signal Range (m)	500
CONNECTIONS	
Side A - Connector 1	SFP+ (MALE)
Side B - Connector 1	LC DUPLEX (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.triplite.com/products/product-certification-agencies>