

NetDirector Serial Server Interface Unit (B064-Series)

MODEL NUMBER: **B055-001-SER**



Description

Tripp Lite's Serial Server Interface Unit connects the DB9 male serial port on a server to a B064-Series NetDirector KVM switch using Cat5e/6 cabling. Use of Cat5e/6 cables frees up space in server cabinets that would otherwise be filled by traditional, bulkier KVM cable kits. Includes a USB cable for powering the unit. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Eliminates the need for thicker, heavier KVM cable kits
- Compact, lightweight design
- Plug and Play; no software required
- Includes a USB cable to power the unit
- Supports VT100 serial emulation
- 492 ft. (150 m.) distance from KVM switch
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- Needed to connect to a DB9 male serial port on a server to a B064-Series NetDirector KVM switch via Cat5e/6 cable
- Easy to install; no software needed
- Allows a maximum distance of 492 ft. (150 m.) from KVM to serial port via Cat5e/6 cable
- Compact and lightweight design
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Server or CPU with a DB9 male serial connector
- A B064-Series NetDirector Cat5 KVM Switch
- Cat5e/6 cable

Package Includes

- B055-001-SER SIU
- USB Cable to power the unit

Specifications

OVERVIEW	
Model Type	Interface Modules
Accessories Type	Server Interface Unit
CONNECTIONS	
Connector A	RJ45 (FEMALE)
Connector B	DB9 (FEMALE)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.