

CYBEX™ SC800/SC900 SECURE DESKTOP DVI-I KVM SWITCHES



Outstanding security and control at the desktop

BENEFITS

- Certified to NIAP Protection Profile for Peripheral Sharing Switches, version 3.0
- Always-on active anti-tampering system
- Unidirectional Optical Data Diodes assure USB peripheral isolation enabling data flow from devices to host only
- Hardware-based peripheral isolation loads all firmware on ROM with no keyboard buffering or memory
- Full USB device filtering to assure support for keyboard and mouse only
- Support for DVI-I in single and dual head models supporting resolutions up to 2560 x 1600
- Mouse and keyboard switching via emulation assures zero delay in switching them between connected sources
- Dedicated Peripheral Port permits a secure connection to external USB devices, including CAC smart card readers, fingerprint readers and face recognition devices



PART NUMBER	SC820/SC920	SC840/SC845/SC940/SC945	SC885/SC985
System Connections	2	4	8
System Support	DVI-I, single-link/dual-link		
Display Connections	Single Head SC8xx, Dual Head SC9xx		
Display Support	DVI-I, single-link/dual-link		
Max Resolution	DVI dual-link - 2560 x 1600 @ 60Hz		
CONNECTIONS			
Console Peripherals	USB Type - A		
Computer Peripherals	USB Type - B		
Dedicated Peripheral Port	0	1 (SC845/SC945)	1
Audio Input/Output	1 x 3.5 mm stereo female		
MECHANICAL			
Enclosure	Steel with plastic front panel		
Dimensions	7 x 2.4 x 1.7 (178 x 61 x 43) SC800	13.7 x 5 x 1.7 (348 x 127 x 43) SC800	17.3 x 7.3 x 1.7 (439 x 185 x 43) SC800
W x D x H in/ (mm)	7 x 2.4 x 2.2 (178 x 61 x 56) SC900	13.7 x 5 x 2.2 (348 x 127 x 56) SC900	17.3 x 7.3 x 2.2 (439 x 185 x 56) SC900
Weight lbs/ (kg)	1.0 (0.5) SC800 / 1.5 (0.7) SC900	3.0 (1.5) SC800 / 3.7 (1.9) SC900	5.4 (2.5) SC800 / 6.8 (3.1) SC900
POWER			
Power Requirements	12V DC, 1.5A Power Adapter	35W Max Internal	45W Max Internal
AC Input Voltage	100 to 240V AC		
ENVIROMENTAL			
Operating Temperature	32° to 104°F; 0° to 40°C		
Storage Temperature	-4° to 140°F; -20° to 60°C		
Humidity	0-80% RH, non-condensing		
Cetifications	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada		
Warranty	3 years		



SC845 rear panel

Cybex™ Desktop DVI-D Cables

PART NUMBER	MODEL	DETAILS
CBL0146	SC845, SC885	USB keyboard, mouse & single head DVI-D with audio & DPP - 6 ft.
CBL0147	SC845, SC885	USB keyboard, mouse & single head DVI-D with audio & DPP - 10 ft.
CBL0148	SC945, SC985	USB keyboard, mouse & dual head DVI-D with audio & DPP - 6 ft.
CBL0149	SC945, SC985	USB keyboard, mouse & dual head DVI-D with audio & DPP - 10 ft.
CBL0150	SC820, SC840	USB keyboard, mouse & single head DVI-D with audio - 6 ft.
CBL0151	SC820, SC840	USB keyboard, mouse & single head DVI-D with audio - 10 ft.
CBL0152	SC920, SC940	USB keyboard, mouse & dual head DVI-D with audio - 6 ft.
CBL0153	SC920, SC940	USB keyboard, mouse & dual head DVI-D with audio - 10 ft.

VertivCo.com | Vertiv Headquarters, 1050 Dearborn Drive, Columbus, OH, 43085, USA

© 2017 Vertiv Co. All rights reserved. Vertiv and the Vertiv logo are trademarks or registered trademarks of Vertiv Co. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness herein, Vertiv Co. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.