

15 ft Mini DisplayPort™ to VGA Adapter Converter Cable – mDP to VGA 1920x1200 - White

StarTech ID: MDP2VGAMM15W



The MDP2VGAMM15W active Mini DisplayPort to VGA converter cable lets you connect your Mini DisplayPort-equipped desktop or laptop directly to a VGA monitor or projector at a longer distance than a standard-length cable would support, while saving the expense of additional adapters. The cable features a stylish white design, that is well-suited for connecting Mac® computers.

Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The MDP2VGAMM15W is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Applications

- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (PC, laptop, Mac, Ultrabook)
- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting

Features

- Active Mini DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal

Technical Specifications

| | |
|-----------------------------|---|
| Warranty | 2 Years |
| Converter Type | Active |
| Adapter Style | Cable Adapter |
| Audio | No |
| Chipset ID | ANALOGIX 9832 |
| Connector A | 1 - Mini-DisplayPort (20 pin) Male |
| Connector B | 1 - VGA (15 pin; High Density D-Sub) Male |
| Maximum Cable Length | 15 ft [4.6 m] |
| Maximum Analog Resolutions | 1920x1200 / 1080p (Output) |
| Maximum Digital Resolutions | 1920x1200 / 1080p (Input) |
| Color | White |
| Cable Length | 15 ft [4.6 m] |
| Product Length | 15 ft [4.6 m] |
| Product Width | 1.3 in [34 mm] |
| Product Height | 0.6 in [15 mm] |
| Product Weight | 8.3 oz [234 g] |
| Operating Temperature | 0°C to 60°C (32°F to 140°F) |
| Storage Temperature | -10°C to 70°C (14°F to 158°F) |
| Humidity | 40%-85%RH |
| Shipping (Package) Weight | 0.5 lb [0.2 kg] |
| Included in Package | 1 - Mini DisplayPort to VGA Adapter Cable |

Certifications, Reports and Compatibility

