

Cisco Channelized T1/E1 and ISDN PRI Modules

Product Overview

The Cisco® Channelized T1/E1 and ISDN PRI High-Speed WAN Modules combine multiple T1/E1 WAN connectivity—Channelized T1/E1 and ISDN Primary Rate Interface (PRI), in the same card. Applications include fractional or full T1/E1 WAN connectivity, ISDN PRI for primary WAN link or WAN backup, and dial access aggregation. With flexible WAN connectivity options, together with integrated routing, security, voice, and wireless capabilities, Cisco Integrated Services Routers can meet every need of enterprise-class branch offices today and in the future. Three versions are available, 1- and 2-port cards (Figure 1) in a single-wide high-speed WAN interface card (HWIC), and a 8-port cards (Figure 2) in a single-wide network module. The different versions help enable customers to deploy different port densities according to the needs of individual offices. The modules can be used in T1 or E1 networks, selectable by software configuration. The integrated channel service unit/data service unit (CSU/DSU) function allows customers to consolidate customer premises equipment (CPE). The modules support balanced and unbalanced E1 connectivity and conform to the G.703 and G.704 standards for unframed and framed E1 modes. The Channelized T1/E1 and ISDN PRI modules work with the digital modem module in the Cisco 2800 and 3800 Series Routers to provide V.90- and V.92-compliant digital dial access aggregation.

The 1- and 2-port Channelized T1/E1 and ISDN PRI HWICs are updated versions of the E1/T1 ISDN PRI network modules, with the same functions and performance in a compact form factor of HWIC. You can save the network module slots for other LAN/WAN connectivity, and your deployment flexibility is greatly enhanced. The 8-port Channelized T1/E1 and ISDN PRI network module expands the scalability of T1/E1 ports on the Cisco 3800 Series. You can use the increased port densities for small-scale WAN aggregation in the regional offices.

Figure 1. 1- and 2-Port Channelized T1/E1 and ISDN PRI High-Speed WAN Interface Card



Figure 2. 8-Port Channelized T1/E1 and ISDN PRI Network Module



Features and Benefits

- 1, 2, or 8 ports of RJ-48
- Cisco IOS® Software configurable for T1 or E1 operation
- Integrated CSU/DSU per port
- Fractional T1/E1 (n x DS-0) or full T1/E1
- Balanced or unbalanced E1 termination in the same module
- E1 unframed and framed modes (G.703 or G.704)
- PRI for data, T1-channel associated signaling (CAS), and E1-CAS R2 signaling
- Interoperable with Cisco digital modem modules with part numbers PVDM2-12DM, PVDM2-24DM, and PVDM2-36DM
- V.54 loopback-compatible
- Support for Multilink Point-to-Point Protocol (PPP) and Multilink Frame Relay (FRF.16)

Key Benefits

Enhanced Flexibility

The Cisco E1/T1 ISDN PRI HWICs are software-configurable between E1 or T1 operation, balanced or unbalanced E1 termination, and CSU/DSU. Customers no longer need to buy a specific module for T1 support and then another card for E1 connectivity. In addition, the same modules provide for balanced (120-ohm) and unbalanced (75-ohm) E1 termination. Table 1 lists available cable adaptors.

Support for G.703 Unstructured E1 Signaling

ITU signaling standard G.703 was previously available only on Cisco midrange routers through the voice/WAN interface card (VWIC-xFT-G703), which did not support data PRI. Framed E1 (G.704) is also supported for international customers without G.703 service.

High-Density PRI Connectivity Options

With the new 8-port Channelized T1/E1 and ISDN PRI modules, the Cisco 3800 Series provide superior performance and port density needed for WAN gateways of small enterprises.

Increased Manageability and Troubleshooting

Critical loopback support makes the Cisco Channelized T1/E1 and ISDN PRI Modules easy to manage. Both models can internally loop back the onboard framer chip toward the interface, thus eliminating the need for an external loopback plug. Local, remote, line, and payload loopbacks,

along with support for V.54 inline loop commands, complement the management features of the Cisco Channelized T1/E1 and ISDN PRI Module.

Reliability

Integrating the external E1/T1 terminating device (CSU/DSU) increases the overall system reliability. Possible points of failure are reduced by eliminating the second power supply, additional fans, extra cabling, and other equipment that accompany a "two-box" solution. This increase in reliability allows service providers to more easily and cost-effectively meet the requirements of their customers' service-level agreements (SLAs) and provides enterprises with maximum equipment uptime.

Product Specifications

Table 1 lists the product numbers of the Cisco Channelized T1/E1 ISDN PRI Modules and the cables for balanced and unbalanced E1.

Table 1. Product Numbers of the Cisco Channelized T1/E1 and ISDN PRI Modules and Cables

Product Number	Description
HWIC-1CE1T1-PRI	1 Port Channelized T1/E1 and ISDN PRI High Speed WAN Interface Card
HWIC-2CE1T1-PRI	2 Port Channelized T1/E1 and ISDN PRI High Speed WAN Interface Card
NM-8CE1T1-PRI	8 Port Channelized T1/E1 and ISDN PRI Network Module
CAB-E1-RJ45BNC	E1 Cable RJ-45 to Dual BNC (Unbalanced)

Platform Support

Refer to the software release notes or the Cisco IOS Software Upgrade Planner, or ask your local Cisco representative for information about supported platforms and minimum software and memory requirements. Table 2 shows the minimum Cisco IOS Software requirements for each platform.

Table 2. Minimum Cisco IOS Software Requirements

Minimum Cisco IOS Software Feature Set	Minimum Cisco IOS Software Release
IP BASE	<ul style="list-style-type: none"> 12.4(11)XW4 12.5T first release (TBD)

Table 3 shows the platform support and maximum number of Cisco Channelized T1/E1 and ISDN PRI Modules supported in each platform.

Table 3. Number of Cisco Channelized T1/E1 and ISDN PRI Modules per Platform

Type of Module	Cisco 1841 and 2801	Cisco 2811, 2821, and 2851	Cisco 3825	Cisco 3845
HWIC-1CE1T1-PRI	X	4	4	4
HWIC-2CE1T1-PRI	X	4	4	4
NM-8CE1T1-PRI	X	X	1	1

X = Not supported

Software and Management Features

Table 4 shows the number of DS-0 channels supported by Cisco Channelized T1/E1 and ISDN PRI HWICs and Network Module. Each port can support up to 24 channels for T1 and 31 channels for E1.

Table 4. Number of DS-0 Channels Supported per Module

Type of Module	Number of DS-0 Channels per Module
HWIC-1CE1T1-PRI	Up to 32 channels on each card
HWIC-2CE1T1-PRI	Up to 64 channels on each card
NM-8CE1T1-PRI	Up to 128 channels on each card

Table 5 shows the management features for the Cisco Channelized T1/E1 and ISDN PRI HWICs and Network Module.

Table 5. Management Features

Feature	Description
Diagnostic Loopback Support	<ul style="list-style-type: none"> • E1 loopback modes: <ul style="list-style-type: none"> ◦ Controller local loopback ◦ Interface local loopback • T1 loopback modes: <ul style="list-style-type: none"> ◦ Interface local loopback ◦ Interface remote loopback ◦ Controller local loopback ◦ Controller remote loopback • CSU loopback modes for T1 CSU: <ul style="list-style-type: none"> ◦ Data terminal equipment (DTE) loopback ◦ Network loopback ◦ Payload loopback ◦ V.54
Alarm Detection	<ul style="list-style-type: none"> • Yellow Alarm-Receive/Send from/to network • Blue Alarm-Receive alarm indication signal (AIS) from network • Red Alarm-Loss of network signal
Relevant MIB Support	<ul style="list-style-type: none"> • T1 MIB (RFC1406-MIB) • Cisco Integrated DSU/CSU MIB (CISCO-ICSUDSU-MIB)
Remote Management	<ul style="list-style-type: none"> • Cisco CNS 2100 Series Intelligence Engine (IE2100) • CiscoWorks
Signaling Debugging	<ul style="list-style-type: none"> • CAS debugs • ISDN Q.921 and Q.931 decode • All other previously existing applicable Cisco IOS Software debugs

Hardware Specifications

Table 6 shows the hardware specifications for the Cisco Channelized T1/E1 and ISDN PRI HWICs and Network Module.

Table 6. Hardware Specifications for the Cisco Channelized T1/E1 and ISDN PRI Modules

Feature	Description
Dimensions (H x W x D)	<ul style="list-style-type: none"> • HWIC-1CE1T1-PRI: 0.75 x 3.08 x 4.74 in. • (1.91 x 7.82 x 12.04 cm) • HWIC-2CE1T1-PRI: 0.75 x 3.08 X 4.74 in. • (1.91 x 7.82 x 12.04 cm) • NM-8CE1T1-PRI: 1.59 x 7.10 x 7.29 in. (4.0 x 18.0 x 18.5 cm)
Weight	<ul style="list-style-type: none"> • HWIC-1CE1T1-PRI: 0.18 lb (0.08 kg) • HWIC-2CE1T1-PRI: 0.19 lb (0.09 kg) • NM-8CE1T1-PRI: 1.4 lb (0.63 kg)
Operating Temperature	32 to 104°F (0 to 40°C)
Nonoperating Temperature	-40 to 185°F (-40 to 85°C)
Relative Humidity	5-95% noncondensing

Feature	Description
LEDs	LEDs per port <ul style="list-style-type: none"> • Carrier Detect/Loopback (CD/LP) : <ul style="list-style-type: none"> ◦ Off = No carrier detect ◦ Green On = Carrier detect ◦ Yellow On = Port in loopback mode • Alarm (AL): <ul style="list-style-type: none"> ◦ Off = No alarms ◦ Yellow On = Port in alarm mode LEDs per module (on NM-8CE1T1-PRI only): <ul style="list-style-type: none"> • EN: <ul style="list-style-type: none"> ◦ Off = Card not available ◦ On = Card enabled
Ports	1, 2, or 8 T1/E1 ports on RJ-48C connectors
Line Bit Rate (per Port)	<ul style="list-style-type: none"> • E1: (2.048 Mbps) • T1: (1.544 Mbps)
Line Coding	<ul style="list-style-type: none"> • E1: High-density bipolar three (HDB3) • T1: Alternate mark inversion (AMI) and binary 8-zero substitution (B8ZS)
Framing Formats	<ul style="list-style-type: none"> • E1: CRC4 • T1: Super Frame (SF) and Extended Super Frame (ESF)
Output Levels	<ul style="list-style-type: none"> • E1: short-haul/long-haul • T1 (line build-out [LBO]): 0, -7.5, or -15 dB

Regulatory Compliance, Safety, Emissions, and EMC/Immunity

Table 7 shows a partial listing of regulatory compliance and safety data.

Table 7. Regulatory Compliance and Safety (partial listing*)

Feature	Description
Telecom compliance	<ul style="list-style-type: none"> • USA: FCC Part 68, TIA-968A • Canada: Industry Canada CS-03 • European Union: TBR 4, TBR 12, TBR 13 • Australia: AS/ACIF S038, AS/ACIF S016 • Japan: JATE Gray Book • Hong Kong: HKTA 2027, HKTA 2015 • Taiwan: IS6100 • Singapore: IDA TS ISDN PRA • Korea: MIC No.2004-15
Telecommunication Interface Industry Standards	ITU-T G.703, G.704, G.706, G.823, and ANSI T1.403
Safety	<ul style="list-style-type: none"> • United States: UL60950 • Canada: C22.2 No.60950 • Europe: EN60950 • Australia and New Zealand: AS/NZS3260 and TS001 • Other countries: IEC60950
Network Equipment Building Standards (NEBS)	GR-63, GR-78, and GR-1089-CORE Type 1/3

Feature	Description
EMC Emissions and Immunity	<ul style="list-style-type: none"> • 47 CFR Part 15: 2005 • CISPR22: 2005 • EN300386: V1.3.3 : 2005 • EN55022: 1994 [+ amd 1 & 2] • EN55022: 1998 • EN61000-3-2: 2000 [Inc amd 1 & 2] • EN61000-3-3: 1995 [+ amd 1: 2001] • ICES-003 Issue 4 : 2004 • KN 22: 2005 • VCCI: V-3/2006.04 • CISPR24: 1997 [+ amd 1 & 2] • EN300386: V1.3.3 : 2005 • EN50082-1: 1992 • EN50082-1: 1997 • EN55024: 1998 [+ amd 1 & 2] • EN61000-6-1: 2001

For more information, visit the Cisco Compliance home page (listed later in this document in the section "Country Support") or consult your local Cisco representative.

Safety, EMC, Telecom, Network Homologation, Power, Environmental Requirements, and Regulatory Approvals

When installed in a Cisco 2800 or 3800 Series Router, the 1- and 2-port Channelized T1/E1 and ISDN PRI HWICs and 8-port Channelized T1/E1 and ISDN PRI network module do not change the standards (safety, EMC, telecom, network homologation, power, environmental requirements, and regulatory approvals) of the router itself. Refer to the Cisco 2800 and 3800 Series data sheets for additional information about mechanical, environmental, and agency certifications.

- For Cisco 2800 Series: <http://www.cisco.com/en/US/partner/products/ps5854/index.html>
- For Cisco 3800 Series: http://www.cisco.com/en/US/prod/collateral/routers/ps5855/product_data_sheet0900aecd8016a8e8.html

Country Support

Visit the following URL or contact your local Cisco representative for country-specific approval status (Cisco.com login required): <http://www.cisconfax.com>.



Americas Headquarters
 Cisco Systems, Inc.
 170 West Tasman Drive
 San Jose, CA 95134-1706
 USA
www.cisco.com
 Tel: 408 526-4000
 800 553-NETS (6387)
 Fax: 408 527-0883

Asia Pacific Headquarters
 Cisco Systems (USA) Pte. Ltd.
 168 Robinson Road
 #28-01 Capital Tower
 Singapore 068912
www.cisco.com
 Tel: +65 6317 7777
 Fax: +65 6317 7799

Europe Headquarters
 Cisco Systems International BV
 Haarlerbergpark
 Haarlerbergweg 13-19
 1101 CH Amsterdam
 The Netherlands
www-europe.cisco.com
 Tel: +31 0 800 020 0791
 Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)