

1 Port USB to RS232 DB9 Serial Adapter Cable - M/M

StarTech ID: ICUSB232V2



The ICUSB232V2 1 Port USB to Serial Adapter converts a USB port into an RS232 DB9 serial port to connect to, monitor, and control a serial device.

Supporting data transfer rates up to 921.6 Kbps, the USB to serial cable is a convenient and cost-saving solution for providing serial connectivity to devices such as point-of-sale terminals, serial modems, industrial equipment, and a wide variety of other RS232 peripherals.

The USB to RS232 converter is easy to install and offers broad operating system compatibility, including Windows® 8, Linux and Mac OS®, for easy integration into mixed environments.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port
- Connect bar code scanners, receipt printers and other point of sale devices
- Connect, monitor and control industrial/automotive sensors and other sensitive equipment
- Connect and program LED and digital signage boards

Features

- USB to Straight-Through RS232 DB9 Serial Adapter
- High-speed 921.6Kbps Baud Rate
- Compatible with Windows® 8, Mac OS X® and Linux

Technical Specifications

Warranty	3 Years
Ports	1
Interface	Serial
Bus Type	USB 2.0
Port Style	Cable Adapter
Industry Standards	USB 1.1/2.0 RS232
Chipset ID	Prolific - PL2303-HXD
Connector Type(s)	1 - DB-9 (9 pin; D-Sub) Male
Connector Type(s)	1 - USB A (4 pin) Male
Serial Protocol	RS-232
Max Baud Rate	921.6 Kbps
Data Bits	5, 6, 7, 8
FIFO	512 Bytes
Flow Control	None, Xon/Xoff, RTS/CTS, DTR/DSR
Parity	Odd, Even, Mark, Ace, or None Parity Modes
Stop Bits	1, 1.5, 2
OS Compatibility	Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), 2000 Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.x (Tested up to 10.10), 9.x, 8.x Linux 2.4.31 and later
Microsoft WHQL Certified	Yes
System and Cable Requirements	One available USB 1.1 (or above) port
Enclosure Type	Plastic
Product Length	16.9 in [430 mm]
Product Width	1.4 in [35 mm]
Product Height	0.8 in [20 mm]
Product Weight	1.9 oz [52.5 g]
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-20°C to 80°C (-4°F to 176°F)
Humidity	0~65% RH
Shipping (Package) Weight	2.2 oz [62.5 g]
Included in Package	1 - USB to RS232 Adapter
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

