

USB DVI over Cat 5e / Cat 6 KVM Console Extender w/ 1920x1200 Uncompressed Video - 330ft (100m)

StarTech ID: SV565UTPDUV



The SV565UTPDUV USB DVI KVM Extender lets you control a PC from up to 330ft (100m) away over a single Cat 5e or Cat 6 cable connection, with uncompressed 1920x1200 DVI video and access to up to 3 connected USB devices.

A flexible solution for powering large high-definition displays remotely, this DVI USB extender supports uncompressed 1920x1200 video resolution at maximum distance, with 24-bit color depth.

This versatile KVM console extender can be connected to a single system, or cascaded to an existing KVM switch for remote operation of multiple systems, and features 3 USB 2.0 ports on the remote end, allowing you to connect a keyboard, mouse, printer or other peripherals. Since the extender uses Cat 5e (or better) network cable, you have the option to use existing infrastructure wiring, which helps avoid the hassle and expense of running bulky video cables.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Operate one or more servers from a remote location within the same building or campus
- Use for remote control of secured, physically inaccessible servers
- Can act as a thin client for power users controlling powerful rack mounted servers as their desktop machines
- Control and monitor a remote server from a harsh environment where the PC would not function properly due to heat/dust/etc. (factory, warehouse, mining, etc.)
- Ideal for controlling a PC in an area where fan or hard drive noise is unacceptable such as a television broadcast studio

Features

- Uncompressed 1920x1200 HD video extension
- Extend up to 330 ft (100m) over a single Cat5e / Cat6 cable
- OS independent - no software or drivers required
- 3 USB 2.0 ports with transfer rates up to 30Mbps
- Supports connection to a single computer or cascading to an existing KVM switch
- Supports most combo keyboard and mouse sets (including Wireless)

Technical Specifications

Warranty	2 Years
Audio	No
KVM Ports	1
PC Interface	USB
PC Video Type	DVI
Multi-Monitor	No
Rack-Mountable	No
Daisy-Chain	Yes
Console Interface(s)	1 - DVI-D (25 pin) Female
Console Interface(s)	1 - RJ-45 Female
Console Interface(s)	3 - USB A (4 pin) Female
Host Connectors	1 - DVI-D (25 pin) Female
Host Connectors	1 - RJ-45 Female
Host Connectors	1 - USB B (4 pin) Female
IP Control	No
Maximum Data Transfer Rate	30 Mbps (USB)
Max Transfer Distance	100 m (328 ft)
Maximum Digital Resolutions	Full Uncompressed 1920x1200
Color Depth	24-bit, 16.7M colors (Truecolor)
OS Compatibility	OS independent; No software or drivers required
Note	Product measurements indicate a single unit only (either Host or Remote)
Color	Black
Enclosure Type	Aluminum
Product Length	6.9 in [175 mm]
Product Width	4.6 in [118 mm]
Product Height	1.2 in [30 mm]
Product Weight	30.3 oz [857 g]
LED Indicators	1 - Power
LED Indicators	1 - Link
LED Indicators	1 - USB
LED Indicators	1 - Video
Power Source	2 AC Adapters Included
Input Voltage	100 ~ 240 AC

Input Current	0.6 A
Output Voltage	5 DC
Output Current	3 A
Center Tip Polarity	Positive
Plug Type	M
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Humidity	20~80% RH (Non-Condensing)
Shipping (Package) Weight	5.5 lb [2.5 kg]
Included in Package	1 - Local Extender Unit
Included in Package	1 - Remote Extender Unit
Included in Package	2 - Mounting Brackets
Included in Package	1 - DVI Cable
Included in Package	1 - USB Cable
Included in Package	2 - Universal Power Adapters
Included in Package	6 - Power Cords (2 sets, NA/EU/UK)
Included in Package	1 - Quick Start Guide

Certifications, Reports and Compatibility



OperatingSystem
Independent

 **RoHS Compliant**
Available